



600-HP : Compact High-Power Subwoofer



600-HP shown with optional QuickFly MRF-600 rigging frame

Dimensions	41.40" w x 22.50" h x 22" d (1052 mm x 572 mm x 559 mm)
Weight	182 lbs (82.55 kg); with rigging: 215 lbs (97.52 kg)
Enclosure	Premium birch plywood
Finish	Black textured
Protective Grille	Powder-coated, hex stamped steel lined with acoustical black mesh
Rigging	Optional end-mounted QuickFly® rigging hardware, with captive GuideALinks™ on the bottom four corners and quick-release pins; compatible with MICA™ compact high-power curvilinear array loudspeakers and accessories

The 600-HP is a self-powered, high-output subwoofer that may be used in both flown and ground-stacked configurations. It is designed to rig directly with MICA compact, high-power curvilinear array loudspeakers when fitted with the optional QuickFly MRF-600 rigging frame. The versatility of the 600-HP also allows it to be used with a variety of other Meyer Sound self-powered loudspeakers — such as CQ-1, CQ-2, UPA-1P, UPA-2P and UPJ-1P — in fixed and touring applications.

The system features two specially designed high-power 15-inch cone drivers, engineered to provide optimal performance in subwoofer applications. The high-excursion, back-vented drivers have 4-inch voice coils, and each is rated to handle 1200 watts (AES*).

Each cone driver is driven by a channel of the integral two-channel class AB/H amplifier with complementary MOSFET output stages. Total power is 2250 watts (4000 watts peak), and the operating frequency range is from 33 Hz to 150 Hz, with a peak SPL of 138 dB. An amplifier with integral signal processing and driver protection is integrated into a field-replaceable module mounted in the rear of the enclosure.

The optional MRF-600 rigging frame uses captive, rigid GuideALinks. A slot and convenient pinned handle allow the links to be moved and pinned for arraying or storage. The 600-HP can make use of the optional MG-MICA rigging grid for flown and stacked configurations. The exterior dimensions of the 600-HP enclosure

are suitable for both U.S. and European trucks, and can travel securely in stacks using the MCF-MICA caster frame.

The 600-HP is available with or without QuickFly rigging hardware or handles; all versions include plastic skids on the bottom of the unit to ensure secure stacking and prevent damage to the enclosure. Options for the 600-HP include weather protection, and custom color finishes for fixed installations and other applications requiring specific cosmetics. The RMS™ remote monitoring system — standard with the rigging version and optional on other configurations — allows comprehensive monitoring of system parameters on a Windows®-based network.

*Driven continuously for two hours with a band-limited noise signal having a 6 dB peak-to-average ratio.

FEATURES & BENEFITS

- Efficient, high-power and high-excursion cone drivers
- Extremely low distortion for low-frequency clarity
- Very high peak power yields excellent transient reproduction
- Stackable, and flyable by itself or with MICA full-range loudspeakers
- Compatible with MG-MICA rigging frame for flying and ground-stacking
- Transportable in stacks using optional MCF-MICA caster frame
- Low-frequency complement to MICA and other Meyer Sound self-powered loudspeakers

APPLICATIONS

- Medium to large theatres and clubs
- Houses of worship
- Portable and installed A/V systems

SPECIFICATIONS

Operating Frequency Range¹	33 Hz – 150 Hz
Frequency Response²	39 Hz – 130 Hz ±4 dB
Maximum Peak SPL³	138 dB
Coverage	360° (single unit); varies with number of units and configuration
Transducer: Low Frequency	Two 15" cone drivers with 4" voice coil, 1200 W (AES) ⁴
Amplifier Power⁵	2250 W (4000 W peak)
Automatic Voltage Selection	85 – 134 V AC; 165 – 264 V AC; 50/60 Hz
Audio Connector	Female XLR input with male XLR loop output or VEAM all-in-one (integrates AC, audio and network)
AC Connector	250 V AC NEMA L6-20 twistlock, IEC-309 male, PowerCon, or VEAM
Max. Long-Term Cont. Current Draw (>10 sec)	8.8 A rms (115 V AC); 4.4 A rms (230 V AC); 10 A rms (100 V AC)

- NOTES:**
1. Recommended maximum operating frequency range. Response depends upon loading conditions and room acoustics.
 2. Measured with 1/3 octave frequency resolution at 4 meters, free field.
 3. Measured with music referred to 1 meter, half-space loading.
 4. Power handling is measured under AES standard conditions: transducer driven continuously for two hours with band-limited noise signal having a 6 dB peak-average ratio.
 5. Amplifier wattage rating based on the maximum unclipped burst sine-wave rms voltage that the amplifier will produce for at least 0.5 seconds into the nominal load impedance. Both channels 67 V rms (95 V pk) into 4 ohms. Peak power based on the maximum unclipped peak voltage that the amplifier will produce for at least 100 milliseconds into the nominal load impedance.

Made by Meyer Sound Laboratories
Berkeley, California USA
European Office:
Meyer Sound Lab. GmbH
Carl Zeiss Strasse 13
56751 Polch, Germany



600-HP: 04.149.010.01 A

©2005
Meyer Sound Laboratories Inc.
All rights reserved.

MEYER SOUND LABORATORIES INC.
2832 San Pablo Avenue
Berkeley, CA 94702

T: +1 510 486.1166
F: +1 510 486.8356

info@meyersound.com
www.meyersound.com